

CORRIGENDUM -V Dated: 03.11.2021

Attention is invited to tender No. S-CEM/OTE/EMCD/1080-LE/102-06/21-22/11739 dated 11.08.2021 for the **Supply, Installation, Commissioning, Performance testing and validation of Conducted & Radiated Emission and Conducted Susceptibility Automated Test Systems**. Technical Specifications and commercial terms have been revised after pre-bid meeting held on 18.08.2021.

TENDER NO.: S-CEM/OTE/EMCD/1080-LE/102-06/21-22/11739																
Supply, installation, Commissioning, Performance testing and validation of Conducted & Radiated Emission and Conducted Susceptibility Automated Test Systems																
Sl. No	Page No.	Clause No.	Published as:	Revised as:												
10	<u>CORRIGE NDUM III</u> <u>Dated: 29.09.2021</u>	B.6	Band Rejection notch filter Network set	Band Rejection notch filter Network set												
			<table border="1"> <tr> <td>Frequency range</td> <td>10kHz-10GHz(in various band)</td> </tr> <tr> <td>Rejection</td> <td>50dB(minimum)</td> </tr> <tr> <td>Connector</td> <td>N Female</td> </tr> </table>	Frequency range	10kHz-10GHz(in various band)	Rejection	50dB(minimum)	Connector	N Female	<table border="1"> <tr> <td>Frequency range</td> <td>10kHz-10GHz(in various bands to cover the full frequency range)</td> </tr> <tr> <td>Rejection</td> <td>50dB(minimum)</td> </tr> <tr> <td>Connector</td> <td>N Female</td> </tr> </table>	Frequency range	10kHz-10GHz(in various bands to cover the full frequency range)	Rejection	50dB(minimum)	Connector	N Female
Frequency range	10kHz-10GHz(in various band)															
Rejection	50dB(minimum)															
Connector	N Female															
Frequency range	10kHz-10GHz(in various bands to cover the full frequency range)															
Rejection	50dB(minimum)															
Connector	N Female															
11	<u>CORRIGE NDUM III</u> <u>Dated: 29.09.2021</u>	B.7, B.8, and B.9	B.7 Bi Directional Attenuators	B.7 Bi Directional/Unidirectional Attenuators												
			<table border="1"> <tr> <td>Frequency</td> <td>DC-2.4GHz</td> </tr> <tr> <td>Attenuation</td> <td>40 dB</td> </tr> <tr> <td>Average Power</td> <td>300W</td> </tr> </table>	Frequency	DC-2.4GHz	Attenuation	40 dB	Average Power	300W	<table border="1"> <tr> <td>Frequency</td> <td>DC-2.4GHz</td> </tr> <tr> <td>Attenuation</td> <td>40 dB</td> </tr> <tr> <td>Average Power</td> <td>300W</td> </tr> </table>	Frequency	DC-2.4GHz	Attenuation	40 dB	Average Power	300W
Frequency			DC-2.4GHz													
Attenuation			40 dB													
Average Power			300W													
Frequency			DC-2.4GHz													
Attenuation	40 dB															
Average Power	300W															
	B.8 Bi Directional Attenuators	B.8 Bi Directional/Unidirectional Attenuators														
	<table border="1"> <tr> <td>Frequency</td> <td>1-18GHz</td> </tr> <tr> <td>Attenuation</td> <td>30,40 dB</td> </tr> <tr> <td>Average Power</td> <td>150W</td> </tr> </table>	Frequency	1-18GHz	Attenuation	30,40 dB	Average Power	150W	<table border="1"> <tr> <td>Frequency</td> <td>1-18GHz</td> </tr> <tr> <td>Attenuation</td> <td>30,40 dB</td> </tr> <tr> <td>Average Power</td> <td>150W</td> </tr> </table>	Frequency	1-18GHz	Attenuation	30,40 dB	Average Power	150W		
Frequency	1-18GHz															
Attenuation	30,40 dB															
Average Power	150W															
Frequency	1-18GHz															
Attenuation	30,40 dB															
Average Power	150W															
	B.9 Bi Directional Attenuators	B.9 Bi Directional/Unidirectional Attenuators														
	<table border="1"> <tr> <td>Frequency</td> <td>18-40GHz</td> </tr> <tr> <td>Attenuation</td> <td>10dB, 20 dB</td> </tr> <tr> <td>Average Power</td> <td>20W</td> </tr> </table>	Frequency	18-40GHz	Attenuation	10dB, 20 dB	Average Power	20W	<table border="1"> <tr> <td>Frequency</td> <td>18-40GHz</td> </tr> <tr> <td>Attenuation</td> <td>10dB, 20 dB</td> </tr> <tr> <td>Average Power</td> <td>20W</td> </tr> </table>	Frequency	18-40GHz	Attenuation	10dB, 20 dB	Average Power	20W		
Frequency	18-40GHz															
Attenuation	10dB, 20 dB															
Average Power	20W															
Frequency	18-40GHz															
Attenuation	10dB, 20 dB															
Average Power	20W															