

L I M I T E D T E N D E R
N O T I C E

Tender Ref. No.	Date	Tender Due Date
PUR-12/11/2020-MCAD_DIV_SAM_CHE-SMR CHE DEPTT-10016	18-11-2020	02-12-2020

To

Dear Sir,

The Purchase Officer, SAMEER-Centre for Electromagnetics invites sealed tender for the supply of materials as per details given below:

Sl. No	Description of Items	Qty (Nos.)
1	Isolator 1 - for the frequency range 700-1000MHz (As per Specification Attached)	5
2	Isolator 2 - for the frequency range 1700-2700MHz (As per Specification Attached)	5

Terms and Conditions:

- Price quoted should be on the basis of Destination delivery at Perungudi Campus, Chennai 600 096.
- Delivery / Completion period should be clearly indicated.
- Excise Duty, GST Percentage should be clearly indicated if admissible. Not eligible for FORM 'C' / 'D'
- WE ARE EXEMPTED FROM EXCISE DUTY
- Quotation should be valid for atleast 60 days from the date of opening of the tender
- Quotation should be sent in sealed envelope super scribing the tender reference number and tender due date.
YOUR OFFER WILL NOT BE CONSIDERED IF OUR TENDER REFERENCE NO. &
TENDER DUE DATE IS NOT MENTIONED ON COVER.
- Late tenders will not be accepted under any circumstances
- We reserve the right to accept or reject any quotations fully or partly without assigning any reasons.
- For Further Clarification Please Contact 044-22544061 / 22544020 Email: purchase.chn.sameer@nic.in
- Unsolicited bids shall not be considered

P. Ramamoorthi
(P.Ramamoorthi)
Head – Administration
Contd.,



ELECTRONICS INDIA
Billion Products. Million Opportunities.

CIT Campus, 2nd Cross Road, Taramani, Chennai - 600 113, India

सी.आई.टी.परीसर, दूसरा क्रॉस रोड, तारामणी चेन्नै - ६०० ११३.

दूरध्वनि : Tel : +91-44-22541583 / 1817 / 2106 / 2452 फैक्स / Fax : 2254 1938 / 1424

वेबसाईट / web: <http://www.sameer.gov.in> ई-मेल / E-mail: pd@cem.sameer.gov.in

Specification of Isolators

Isolator 1 - for the frequency range 700-1000MHz

Specification for Isolator - 1	
Frequency (GHz)	0.700 to 1.000
Insertion Loss(dB)Max.	0.5
Isolation(dB)MIN	17.0
Return Loss(dB)MIN	17.0
Power FWD/REV (Watt)	10/10
Operating Temperature(°C)	0 to + 50

Isolator 2 - for the frequency range 1700-2700MHz

Specification for Isolator - 2	
Frequency (GHz)	1.700 to 2.700
Insertion Loss(dB)Max.	0.5
Isolation(dB)MIN	17.0
Return Loss(dB)MIN	17.0
Power FWD/REV (Watt)	10/10
Operating Temperature(°C)	0 to + 50